

**VT 406** 

**BIOMEDICAL CHEST FREEZER** 

The VT low temperature freezers creates the possibility to maintain temperatures as low as -45°C. Supreme stability, reliability, user-friendliness and ease of cleaning make these freezers an ideal solution for laboratories and hospitals.



DIMENSIONS	
	VALUE
Outer Dimensions, HxWxD	885x1562x605
Inner Dimensions, HxWxD	635x1400x440
Weight Gross/Net, kg	83,2 / 77,2
Material Inner Cabinet	Painted Steel
Material Outer Cabinet	Painted Steel
Insulation Thickness, mm	80
Insulation Type	Polyurethane with Cyclopentane
Mobility / Castors	Yes
Refrigerant, Type	R290
Number of compressors	1
Internal Air Distribution	Static
Number of Probes	ا
CONTROLLER	VALUE
Controller	XR30CX
Controller language	No language - only 3 digits
USB Connection	No
Logging	No
Temperature Graph	No
High/Low Temp. Alarm	Yes
Open Door Alarm	No
Probe Failure Alarm	Yes
Power Failure Alarm	No
	110
STORAGE	VALUE
Volume, Gross/net, L	384
Baskets	
Basket material	Steel coated with plastic powder
Innerlids	
	No
FEATURES	VALUE
Lock	Yes
LED Light	No
Battery Backup for Controller, 24h	No
Porthole	Yes - Ø 12 mm
Porthole Dry Contact	Nc
	Solid
Door	
Door Reversibility	N/A

1

Products are subject to change due to enhancements and continuous development. Vestfrost Solutions reserve the right to alter any information, without further notice.



## **BIOMEDICAL CHEST FREEZER**

**VT 406** 

The VT low temperature freezers creates the possibility to maintain temperatures as low as -45°C. Supreme stability, reliability, user-friendliness and ease of cleaning make these freezers an ideal solution for laboratories and hospitals.

Frequency	Hz	50Hz
Max Ambient	°C	30°C
Max Humidity	% rh	55%
PERFORMANCE	UNIT	VALUE
All data in RT20°C		
Temperature Range	°C	Fra - 25 til - 45
Uniformity in performance - difference +/- from Avg set point	°C	-
Pull down time (from 25 to fabric setpoint)	Minutes	v. 30 °C, 195
Hold over time (From fabric SP to -25, -40 and -60) Empty	Minutes	-
Refrigerant		R290
Number of probes	pcs	1
Defrost	y/n	No
Internal air distribution		Static
Number of compressors	pcs	1
Safety thermostat	y/n	No
Energy 24 hours	kWh/24h	v. 26 °C, 4,09
Energy year	kWh/year	v. 26 °C, 1492,85

Products are subject to change due to enhancements and continuous development. Vestfrost Solutions reserve the right to alter any information, without further notice.



2