

The VT low temperature freezers creates the possibility to maintain temperatures as low as -45°C. Supreme stability, reliability, user-friendliness and ease of cleaning make these freezers an ideal solution for laboratories and hospitals.



DIMENSIONS		
Outer Dimensions HxWxD, mm	885x1265x605	
Inner Dimensions HxWxD, mm	635x1100x440	
Weight Gross/Net, kg	76,8 / 71,1	
Material inner cabinet	Painted Steel	
Material outer cabinet	Painted Steel	
Packaging weight, kg	-	
Packaging dimensions HxWxD, mm	-	
Insulation thickness, mm	80	
Insulation type	Polyurethane with Cyclopentane	
Mobility / Castors	Yes	
Refrigerant, Type	R290	
Number of compressors	1	
Internal Air Distribution	Static	
Number of Probes	1	
CONTROLLER		
Controller	XR30CX	
Controller language	No language - only 3 digits	
USB Connection	No	
Logging	No	
Temperature Graph	No	
High/Low Temp. Alarm	Yes	
Open Door Alarm	No	
Probe Failure Alarm	Yes	
Power Failure Alarm	No	
STORAGE		
Volume, Gross/net, L	296	
Baskets	1	
Basket material	Steel coated with plastic powder	
Innerlids	No	
FEATURES		
Lock	Yes	
LED Light	No	
Battery Backup for Controller, 24h	No	
Porthole	Yes - Ø 12 mm	
Dry Contact	No	
Door	Solid	
Door Reversibility	N/A	
-	· · · · · · · · · · · · · · · · · · ·	



BIOMEDICAL

The VT low temperature freezers creates the possibility to maintain temperatures as low as $^{-}45^{\circ}\text{C}$. Supreme stability, reliability, user-friendliness and ease of cleaning make these freezers an ideal solution for laboratories and hospitals.

Frequency	Hz	50Hz
Max Ambient	°C	30°C
Max Humidity	% rh	55%
PERFORMANCE		
All data in RT20°C		
Temperature Range	°C	-25 to -45
Uniformity in performance - difference +/- from Avg set point	°C	-
Pull down time (from 25 to factory setpoint)	Minutes	130
Hold over time (from factory SP to -25, -40 and -60) Empty	Minutes	-
Refrigerant		R290
Number of probes	pcs	1
Defrost	y/n	No
Internal air distribution		Static
Number of compressors	pcs	1
Safety thermostat	y/n	No
Energy 24 hours	kWh/24h	-
Energy year	kWh/year	-