

## **VT 306**

## **LOW TEMPERATURE CHEST FREEZER**

The VT low temperature freezers creates the possibility to maintain temperatures as low as -60°C. Supreme stability, reliability, user-friendliness and ease of cleaning make these freezers an ideal solution.





DIMENSIONS	
Outer Dimensions, HxWxD	885x1265x60
Inner Dimensions, HxWxD	635x1100x44
Weight Gross/Net, kg	73,2 / 67,
Material Inner Cabinet / Material Outer Cabinet	Painted Steel / Painted Stee
Insulation Thickness, mm	8
Insulation Type	Polyurethane with Cyclopentan
Mobility / Castors	Ye
Number of compressors	
Internal Air Distribution	Stat
Number of Probes	
STORAGE	
Volume, Gross/net, L	29
Baskets	
Basket material	Steel coated with plastic powde
Innerlids	N
COOLING SYSTEM	
Refrigerant / amount, g	R2S
Energy consumption, kWh/24h	
Energy consumption, kWh/year	
Noise dB	
Voltage, V / Frequency, Hz	-/5
Temperature range, °C	-25 to -4
Energy class	
Uniformity in performance - difference +/- from Avg set point , °C	
Pull down time (from 25 to factory setpoint), min.	13
Hold over time (From factory SP to -25, -40 and -60) Empty, min.	
FEATURES	
Lock	Ye
LED Light	N
Battery Backup for Controller, 24h	N
Porthole	Yes - Ø 12 m
Dry Contact	N
Door	Sol
Door Reversibility	N/
Defrost	N
Safety thermostat	N
CONTROLLER	
Controller	XR30C
Controller language	No language - only 3 digi
USB Connection	N
Logging	N
Temperature Graph	N
High/Low Temp. Alarm	Ye
Open Door Alarm	
Probe Failure Alarm	Yı
Power Failure Alarm	1