

VT 307 LOW TEMPERATURE CHEST FREEZER

The VT low temperature freezers creates the possibility to maintain temperatures as low as -60°C. Supreme stability, reliability, user-friendliness and ease of cleaning make these freezers an ideal solution.



DIMENSIONS	
Outer Dimensions, HxWxD	885x1265x605
Inner Dimensions, HxWxD	635x1100x440
Weight Gross/Net, kg	75,8 / 70,8
Material Inner Cabinet / Material Outer Cabinet	Painted Steel / Painted Stee
Insulation Thickness, mm	80
Insulation Type	Polyurethane with Cyclopentane
Mobility / Castors	Ye
Number of compressors	
Internal Air Distribution	Stati
Number of Probes	
STORAGE	
Volume, Gross/net, L	299
Baskets	
Basket material	Steel coated with plastic powde
Innerlids	No
COOLING SYSTEM	
Refrigerant / amount, g	Nature I
Energy consumption, kWh/24h	5,56
Energy consumption, kWh/year	2030,1
Noise dB	
Voltage, V / Frequency, Hz	- / 50
Temperature range, °C	-40 to -60
Energy class	
Jniformity in performance - difference +/- from Avg set point , °C	5,
Pull down time (from 25 to factory setpoint), min.	16
Hold over time (From factory SP to -25, -40 and -60) Empty, min.	75-83
FEATURES	
Lock	Ye
LED Light	N
Battery Backup for Controller, 24h	N
Porthole	Yes - Ø 12 mn
Dry Contact	N
Door	Solic
Door Reversibility	N//
Defrost Safety thermostat	No.
CONTROLLER	No
Controller	XR30C
Controller language	No language - only 3 digit
USB Connection	No language - only s algu
Logging	No
Temperature Graph	N.
High/Low Temp. Alarm	Ye
Open Door Alarm	
Open Door Alarm Probe Failure Alarm	No Ye

1

Products are subject to change due to enhancements and continuous development. Vestfrost Solutions reserve the right to alter any information, without further notice.

