

EQUIPMENT

The icelined refrigerator series has a built-in heating element ensuring that the appliance can maintain stable temperatures between +2° to +8°C in all ambient temperatures, setting a new industry standard between the DOS requirement. beyond the PQS requirement.

Watch product video here: ICELINED REFRIGERATOR SERIES

All our VLS AC models are PQS certified according to the newest performance standards. Our fully integrated remote equipment monitoring system (EMS) can be added as an option for this model.





DIMENSIONS	VALUE
Height, mm	950
Width, mm	550
Depth, mm with handle	650
Gross weight, kg	84,70
Net weight, kg	63,80
SPECIFICATIONS	VALUE
Gross volume, L	50
Net volume, L	38
Temperature range (43C AMB)	+2 to +8C
Hold-over time, hours	57,52
Energy consumption - stable, kWh/24h	0.504
Energy consumption - cool down, kWh/24h	R600a
Refrigerant	A
Freeze protection, grade	Т
Climae class	E003/120
WHO PQS code	E003/110
FEATURES	VALUE
Storage baskets, no	
Temperature control	Automatic
Lock + keys	YES
Junction box	YES
Adjustable legs	YES, 10cm
Safety thermostat	YES
Appliance plugs	M,G,F
Industrial grade locking mechanism	YES
LOADING QUANTITIES	VALUE
Qty. per 20' / 40/ container	44/92
VOLTAGE REGULATION RANGE	VALUE
	_
220-240V/50/60Hz 100-127V/50/60Hz	110-278V/50/60Hz
100-12/V/50/60HZ	82-159V/50/60Hz