

COLD CHAIN

EQUIPMENT

The icelined refrigerator series has a built-in heating element ensuring that the applicance can maintain stable temperatures between $+2^{\rm o}$ to $+8^{\rm o}{\rm C}$ in all ambient temperatures, setting a new industry standard beyond the PQS requirement.

Watch product video here: ICELINED REFRIGERATOR SERIES





DIMENSIONS	VALUE
Height, mm	910
Width, mm	156
Depth, mm with handle	70
Gross weight, kg	19.
Net weight, kg	17.
SPECIFICATIONS	VALUE
Gross volume, L	314
Net volume, L	24:
Temperature range (43C AMB)	+2 to +80
Hold-over time, hours	55.
Energy consumption - stable, kWh/24h	0.6
Energy consumption - cool down, kWh/24h	N/.
Refrigerant	R600
Freeze protection, grade	
Climae class	
WHO PQS code	E003/11:
FEATURES	VALUI
Storage baskets, no	
Temperature control	Automati
Lock + keys	YE
Junction box	YE
Adjustable legs	YES, 10cn
Safety thermostat	YE
Appliance plugs	M,G,
Industrial grade locking mechanism	YE
LOADING QUANTITIES	VALU
Qty. per 20' / 40/ container	18 / 4
VOLTAGE REGULATION RANGE	VALUI
220-240V/50/60Hz	110-278V/50/60H
100-127V/50/60Hz	82-159V/50/60H