

VT 307

LOW TEMPERATURE CHEST FREEZER



The VT low temperature freezers creates the possibility to maintain temperatures as low as -60°C. Supreme stability, reliability, user-friendliness and ease of cleaning make these freezers an ideal solution.



DIMENSIONS	VALUE	
Outer Dimensions, HxWxD	885x1265x605	
Inner Dimensions, HxWxD	635xi100x440	
Weight Gross/Net, kg	75,8 / 70,	
Material Inner Cabinet	Painted Stee	
Material Outer Cabinet	Painted Ste	
Insulation Thickness, mm	80	
Insulation Type	Polyurethane with Cyclopentane	
Mobility / Castors	Yes	
Refrigerant, Type	Nature I	
Number of compressors	1	
Internal Air Distribution	Static	
Number of Probes	1	
CONTROLLER	VALUE	
Controller	XR30CX	
Controller language	No language - only 3 digits	
USB Connection	N N	
Logging	N	
Temperature Graph	N	
High/Low Temp. Alarm	Ye	
Open Door Alarm	N	
Probe Failure Alarm	Ye	
Power Failure Alarm	No	
STORAGE	VALUE	
Volume, Gross/net, L	296	
Baskets	3	
Basket material	Steel coated with plastic powder	
Innerlids	No	
FEATURES	VALUE	
Lock	Yes	
LED Light	No	
Battery Backup for Controller, 24h	No	
Porthole	Yes - Ø 12 mm	
Dry Contact	No	
Door	Solid	
Door Reversibility	N/A	





VT 307

LOW TEMPERATURE CHEST FREEZER

The VT low temperature freezers creates the possibility to maintain temperatures as low as -60°C. Supreme stability, reliability, user-friendliness and ease of cleaning make these freezers an ideal solution.

Frequency	Hz	50Hz
Max Ambient	°C	30°C
Max Humidity	% rh	55%
PERFORMANCE	UNIT	VALUE
All data in RT20°C		
Temperature Range	°C	Fra -40 til -60
Uniformity in performance - difference +/- from Avg set point	°C	v 20 °C, 5,0
Pull down time (from 25 to fabric setpoint)	Minutes	v 20 °C, 160
Hold over time (From fabric SP to -25, -40 and -60) Empty	Minutes	v. 20 °C, 75-83
Refrigerant		Nature R
Number of probes	pcs	1
Defrost	y/n	No
Internal air distribution		Static
Number of compressors	pcs	1
Safety thermostat	y/n	No
Energy 24 hours	kWh/24h	v. 20 °C, 5,562
Energy year	kWh/year	v. 20 °C, 2030,13

