

VLS 304A AC ICELINED REFRIGERATOR

The icelined refrigerator series has a built-in heating element ensuring that the appliance can maintain stable temperatures between +2° to +8°C in all ambient temperatures, setting a new industry standard beyond the PQS requirement.

Watch product video here: ICELINED REFRIGERATOR SERIES



All our VLS AC models are PQS certified according to the newest performance standards. Our fully integrated remote equipment monitoring system (EMS) can be added as an option for this model.

| DIMENSIONS | VALUE |
|-----------------------------------------|------------------|
| Height, mm | 910 |
| Width, mm | 920 |
| Depth, mm with handle | 700 |
| Gross weight, kg | 132,20 |
| Net weight, kg | 104,80 |
| SPECIFICATIONS | VALUE |
| Gross volume, L | 157 |
| Net volume, L | 98 |
| Temperature range (43C AMB) | +2 to +80 |
| Hold-over time, hours | 55.5 |
| Energy consumption - stable, kWh/24h | 0.60 |
| Energy consumption - cool down, kWh/24h | 0.69 |
| Refrigerant | R600c |
| Freeze protection, grade | Ą |
| Climae class | Т |
| WHO PQS code | E003/11C |
| | |
| FEATURES | VALUE |
| Storage baskets, no | 4 |
| Temperature control | Automatic |
| Lock + keys | YES |
| Junction box | YES |
| Adjustable legs | YES, 10cm |
| Safety thermostat | YES |
| Appliance plugs | M,G,F |
| Industrial grade locking mechanism | YES |
| LOADING QUANTITIES | VALUE |
| Qty. per 20' / 40/ container | 36 / 72 |
| | VALUE |
| VOLTAGE REGULATION RANGE | |
| 220-240V/50/60Hz | 110-278V/50/60Hz |



Products are subject to change due to enhancements and continuous development. Vestfrost Solutions reserve the right to alter any information, without further notice.