

VT 407 LOW TEMPERATURE CHEST FREEZER

The VT low temperature freezers creates the possibility to maintain temperatures as low as -60°C. Supreme stability, reliability, user-friendliness and ease of cleaning make these freezers an ideal solution.



DIMENSIONS Outer Dimensions, HxWxD Inner Dimensions, HxWxD Weight Gross/Net, kg Material Inner Cabinet Material Outer Cabinet	VALUE 885x1562x605 635x1400x440 86,4 / 80,4 Painted Steel Painted Steel 80
Outer Dimensions, HxWxD Inner Dimensions, HxWxD Weight Gross/Net, kg Material Inner Cabinet	885x1562x605 635x1400x440 86,4 / 80,4 Painted Steel Painted Steel
Inner Dimensions, HxWxD Weight Gross/Net, kg Material Inner Cabinet	635x1400x440 86,4 / 80,4 Painted Steel Painted Steel
Weight Gross/Net, kg Material Inner Cabinet	86,4 / 80,4 Painted Steel Painted Steel
Material Inner Cabinet	Painted Steel Painted Steel
	Painted Steel
Material Outer Cabinet	
	80
Insulation Thickness, mm	00
Insulation Type	Polyurethane with Cyclopentane
Mobility / Castors	Yes
Refrigerant, Type	Nature R
Number of compressors	1
Internal Air Distribution	Static
Number of Probes	1
CONTROLLER	VALUE
Controller	XR30CX
Controller language	No language - only 3 digits
USB Connection	No
Logging	No
Temperature Graph	No
High/Low Temp. Alarm	Yes
Open Door Alarm	No
Probe Failure Alarm	Yes
Power Failure Alarm	No
STORAGE	VALUE
Volume, Gross/net, L	384
Baskets	4
Basket material	Steel coated with plastic powder
Innerlids	No
FEATURES	VALUE
Lock	Yes
LED Light	No
Battery Backup for Controller, 24h	No
Porthole	Yes - Ø 12 mm
Dry Contact	No
Door	Solid
Door Reversibility	N/A



Products are subject to change due to enhancements and continuous development. Vestfrost Solutions reserve the right to alter any information, without further notice.



LOW TEMPERATURE CHEST FREEZER

VT 407

FOOD

The VT low temperature freezers creates the possibility to maintain temperatures as low as -60°C. Supreme stability, reliability, user-friendliness and ease of cleaning make these freezers an ideal solution.

Frequency	Hz	50Hz
Max Ambient	°C	30°C
Max Humidity	% rh	55%
		·
PERFORMANCE	UNIT	VALUE
All data in RT20°C		
Temperature Range	°C	Fra -40 til -60
Uniformity in performance - difference +/- from Avg set point	°C	v. 20 °C, 2,9
Pull down time (from 25 to fabric setpoint)	Minutes	v. 20 °C, 165
Hold over time (From fabric SP to -25, -40 and -60) Empty	Minutes	v. 20 °C, 80-88
Refrigerant		Nature R
Number of probes	pcs	1
Defrost	y/n	No
Internal air distribution		Static
Number of compressors	pcs	1
Safety thermostat	y/n	No
Energy 24 hours	kWh/24h	v. 20 °C, 7,077
Energy year	kWh/year	v. 20 °C, 2583,105

Products are subject to change due to enhancements and continuous development. Vestfrost Solutions reserve the right to alter any information, without further notice.

