



VT 546

BIOMEDICAL CHEST FREEZER

The VT low temperature freezers creates the possibility to maintain temperatures as low as -45°C. Supreme stability, reliability, user-friendliness and ease of cleaning make these freezers an ideal solution for laboratories and hospitals.

-25°C
-45°C



DIMENSIONS

Outer Dimensions HxWxD, mm	932x1664x665
Inner Dimensions HxWxD, mm	670x1500x500
Weight Gross/Net, kg	109 / 93
Material inner cabinet	Painted Steel
Material outer cabinet	Painted Steel
Packaging weight, kg	16
Packaging dimensions HxWxD, mm	1020x1715x785
Insulation thickness, mm	80
Insulation type	Polyurethane with Cyclopentane
Mobility / Castors	Yes
Refrigerant, Type	R290
Number of compressors	1
Internal Air Distribution	Static
Number of Probes	1

CONTROLLER

Controller	XR30CX
Controller language	No language - only 3 digits
USB Connection	No
Logging	No
Temperature Graph	No
High/Low Temp. Alarm	Yes
Open Door Alarm	No
Probe Failure Alarm	Yes
Power Failure Alarm	No

STORAGE

Volume, Gross/net, L	495
Baskets	3
Basket material	Steel coated with plastic powder
Inner lids	No

FEATURES

Lock	Yes
LED Light	No
Battery Backup for Controller, 24h	No
Porthole	Yes - Ø 12 mm
Dry Contact	No
Door	Solid
Door Reversibility	N/A



VT 546

BIOMEDICAL CHEST FREEZER

The VT low temperature freezers creates the possibility to maintain temperatures as low as -45°C. Supreme stability, reliability, user-friendliness and ease of cleaning make these freezers an ideal solution for laboratories and hospitals.

Frequency		
Frequency	Hz	50Hz
Max Ambient		
Max Ambient	°C	30°C
Max Humidity		
Max Humidity	% rh	55%
PERFORMANCE		
All data in RT20°C		
Temperature Range		
Temperature Range	°C	-25 to -45
Uniformity in performance - difference +/- from Avg set point		
Uniformity in performance - difference +/- from Avg set point	°C	2,7
Pull down time (from 25 to factory setpoint)		
Pull down time (from 25 to factory setpoint)	Minutes	169
Hold over time (from factory SP to -25, -40 and -60) Empty		
Hold over time (from factory SP to -25, -40 and -60) Empty	Minutes	136-142
Refrigerant		
Refrigerant		R290
Number of probes		
Number of probes	pcs	1
Defrost		
Defrost	y/n	No
Internal air distribution		
Internal air distribution		Static
Number of compressors		
Number of compressors	pcs	1
Safety thermostat		
Safety thermostat	y/n	No
Energy 24 hours		
Energy 24 hours	kWh/24h	4,158
Energy year		
Energy year	kWh/year	1517,67