

Check 3 - Functionality test procedure - Vestfrost CCE AC appliances.

Check	AC	Outcome	
1	Wait for the delay set off voltage stabilizer 3-6 min	Yes	No
2	Green power light is ON	Yes	No
3	Check that controller display is ON		
4	Feel by hand if the compressor is running after 5 minutes of power ON	Yes	No
5	Feel by hand if the compressor discharge tube is heating up	Yes	No
6	Activate and Note temperature on data logger (Picture to be captured in Vestfrost APP)	°C	
7	Feel by hand if the inner lining/evaporator plate is cooling after 1 hour	Yes	No
8	After 2 hours Note temperature on data logger (Picture to be captured in Vestfrost APP)	°C	

Check 5 - Functionality test procedure - Vestfrost CCE SDD appliances.

Check	SDD	Outcome	
1	Green power light is ON	Yes	No
2	Check that controller display is ON	Yes	No
3	Feel by hand if the compressor is running after 5 minutes of power ON	Yes	No
4	Feel by hand it the compressor discharge tube is heating up	Yes	No
5	Activate and Note temperature on data logger	°C	
	(Picture to be captured in Vestfrost APP)		
6	Feel by hand if the inner lining/evaporator plate is cooling after	Yes	No
	1 hour		
7	After 2 hours Note temperature on data logger		
	(Picture to be captured in Vestfrost APP)		

DK-6705 Esbjerg Ø

CVR. 37101117