

VT 206 LOW TEMPERATURE CHEST FREEZER

The VT low temperature freezers creates the possibility to maintain temperatures as low as -60°C. Supreme stability, reliability, user-friendliness and ease of cleaning make these freezers an ideal solution.





DIMENSIONS	
Outer Dimensions, HxWxD	885x923x605
Inner Dimensions, HxWxD	635x760x440
Weight Gross/Net, kg	63,4 / 58,4
Material Inner Cabinet / Material Outer Cabinet	Painted Steel / Painted Steel
Insulation Thickness, mm	80
Insulation Type	Polyurethane with Cyclopentane
Mobility / Castors	Yes
Number of compressors	1
Internal Air Distribution	Static
Number of Probes	1
STORAGE	
Volume, Gross/net, L	198
Baskets	1
Basket material	Steel coated with plastic powder
Inner lids	No
COOLING SYSTEM	
Refrigerant / amount, g	R290
Energy consumption, kWh/24h	3,14
Energy consumption, kWh/year	1146,1
Noise dB	-
Voltage, V / Frequency, Hz	- / 50
Temperature range, °C	-25 to -45
Energy class	-
Uniformity in performance - difference +/- from Avg set point , °C	6,4
Pull down time (from 25 to factory setpoint), min.	90
Hold over time (From factory SP to -25, -40 and -60) Empty, min.	96
FEATURES	
Lock	Yes
LED Light	No
Battery Backup for Controller, 24h	No
Porthole	Yes - Ø 12 mm
Dry Contact	No
Door	Solid
Door Reversibility	N/A
Defrost	No
Safety thermostat	No
CONTROLLER	VERACY
Controller	XR30CX
Controller language	No language - only 3 digits
USB Connection	No
Logging Tomporative Craph	No
Temperature Graph High/Low Temp. Alarm	No
	Yes
Open Door Alarm Probe Failure Alarm	No
Probe Failure Alarm Power Failure Alarm	Yes
rower runure Alarm	No

1

Products are subject to change due to enhancements and continuous development. Vestfrost Solutions reserve the right to alter any information, without further notice.

