



ULTF-51i

ULT TECHNICAL SPECIFICATIONS

Multi voltage.

BIOMEDICAL



DIMENSIONS	
Outer Dimensions HxWxD, mm	836x699x720
Depth incl. door handle	790
Inner Dimensions HxWxD, mm	310x360x445
Weight Gross/Net, kg	108 / 82
Material inner cabinet	Stainless steel
Material outer cabinet	Painted Steel
Packaging weight, kg	26
Packaging dimensions HxWxD, mm	1050x750x850
Insulation thickness	120
Insulation type	Polyurethane with Cyclopentane
Mobility	2 x adjustable feet, 2 x castors
Refrigerant, Type / gram	Nature R 2/99gr
FEATURES	
Lock	<input checked="" type="checkbox"/>
LED light	<input type="checkbox"/>
Battery Backup for Controller, 24h	<input checked="" type="checkbox"/>
Porthole	<input checked="" type="checkbox"/>
Porthole size	20 mm
Dry contact	<input checked="" type="checkbox"/>
Door reversibility	<input type="checkbox"/>
Vacuum valve	<input checked="" type="checkbox"/>
VIP (Vacuum Insulated Panel)	<input checked="" type="checkbox"/>
STORAGE	
Capacity (L)	50
ALARMS	
High / Low temperature	<input checked="" type="checkbox"/>
Open door	<input checked="" type="checkbox"/>
Power failure	<input checked="" type="checkbox"/>
Probe failure	<input checked="" type="checkbox"/>
COOLING	
Refrigerant	Nature R
Noise	< 48
Voltage	100-240 V
Frequency	50/60 Hz
Temperature range	-20 / -86
Ambient condition	25 °C



ULTF-51i

ULT TECHNICAL SPECIFICATIONS

Multi voltage.

BIOMEDICAL

Voltage/Frequency	Voltage/Hz	100-240 V, 50/60Hz
Max Ambient	°C	32
Max Humidity	% rh	65
PERFORMANCE		
All data in RT20°C		
Temperature Range	°C	-20 to -86
Uniformity in performance - difference between top and bottom	°C	+/- 2,5
Pull down time	Minutes	90 min. to -75°C
Hold over time	Minutes	N/A
Noise	dB	< 48
Energy Consumption, kWh / 24h	kWh/24h	4,34 kWh/24h Set -80
Energy year	kWh/year	1584kWh/y Set -80°C
Instant Power Consumption	kW	PD 0,600/Stable 0,280
Heat Rejection	W	N/A
U-Value	W/m ² K	N/A
COOLING COMPONENTS		
Refrigerant/Amount (gram)		Nature R 2/99gr
Number of compressors	pcs	1
Variable speed compressor	Yes/No	Yes
Internal air distribution (type of)		Static
Evaporator Fan	Yes/No/Variable	No
Condenser Fan	Yes/No/Variable	Yes
Number of probes	pcs	2
Defrost	Yes/No	No
CONTROLLER		
Controller	y/n/optional	Yes
Controller type		i-Care touch
USB Connection	y/n	Yes
Data connection	USB	Yes
Controller abilities		Logging of data & alarms
Controller languages		EN, DE, FR
Temperature curve in controller	y/n	Yes