

VT 407

LOW TEMPERATURE CHEST FREEZER

The VT low temperature freezers creates the possibility to maintain temperatures as low as -60°C. Supreme stability, reliability, user-friendliness and ease of cleaning make these freezers an ideal solution.





Outor Dimoneione HyWyD	005-4500-00
Outer Dimensions, HxWxD	885x1562x60
Inner Dimensions, HxWxD	635x1400x44
Weight Gross/Net, kg	86,4/80
Material Inner Cabinet / Material Outer Cabinet	Painted Steel / Painted Ste
Insulation Thickness, mm	8
Insulation Type	Polyurethane with Cyclopentar
Mobility / Castors	Ye
Number of compressors	
Internal Air Distribution	Stat
Number of Probes	
STORAGE	
Volume, Gross/net, L	38
Baskets	
Basket material	Steel coated with plastic powde
Inner lids	N
COOLING SYSTEM	
Refrigerant / amount, g	Nature
Energy consumption, kWh/24h	7,0
Energy consumption, kWh/year	2583,10
Noise dB	
Voltage, V / Frequency, Hz	-/5
Temperature range, °C	-40 to -6
Energy class	
Iniformity in performance - difference +/- from Avg set point , °C	2
Pull down time (from 25 to factory setpoint), min.	16
Hold over time (From factory SP to -25, -40 and -60) Empty, min.	80-8
FEATURES	
Lock	Y
LED Light	١
Battery Backup for Controller, 24h	N
Porthole	Yes - Ø 12 m
Dry Contact	N
Door	Sol
Door Reversibility	N
Defrost	N
Safety thermostat	1
CONTROLLER	
Controller	XR30C
Controller language	No language - only 3 digi
USB Connection	N
Logging	N
Temperature Graph	١
High/Low Temp. Alarm	Y
Open Door Alarm	N

1